

1. Product and Company Identification

Material name CH158A

Use of the preparation Inkjet printing.

Version # 02

Revision date 03-14-2009 CAS # Mixture

Synonym(s) ColorSpan 0900700-102

Company identification Hewlett-Packard Company 3000 Hanover Street

Palo Alto, CA 94304-1185

United States

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomerinquiries@hp.com

Date preparedMar 14, 2009MSDS number363517

2. Hazards Identification

Emergency overview Contact with skin and eyes may result in irritation.

Acute health effects

Skin contact Contact with skin may result in irritation. Avoid contact with the skin.

Eye contact Contact with eyes may result in irritation. Avoid contact with eyes.

Ingestion Acute ingestion may result in mild gastrointestinal distress. May be harmful if swallowed.

Potential health effects

Routes of exposure Potential routes of exposure to this product are skin and eye contact, ingestion, and

inhalation.

3. Composition / Information on Ingredients

Component/substance	CAS number	% by weight	
2-Pyrrolidone	616-45-5	<15	
Glycerol Ethoxylate	31694-55-0	<5	
1,2-Hexanediol	6920-22-5	<3	
Diethanolamine	111-42-2	<2	
Glycerol	56-81-5	<2	
Isopropanol	67-63-0	<2	
Dyes	Proprietary	1-5	
Minor Ingredients	. ,	<1	
Water	7732-18-5	Balance	

4. First Aid Measures

First aid procedures

Eye contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes. Get medical attention if irritation develops or

persists.



Skin contact In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water.

Wash clothing separately before reuse.

Inhalation In case of accident by inhalation: remove casualty to fresh air and keep at rest. If symptoms

persist, get medical attention.

Rinse mouth out with water. Give several glasses of water. If the material is swallowed, get Ingestion

immediate medical attention or advice -- Do not induce vomiting. If symptoms persist, get

medical attention.

5. Fire Fighting Measures

Flash point and method Not flammable

Hazardous combustion

products

Decomposition of this product may yield oxides of sulfur and nitrogen.

Flammable properties The product is not flammable.

Extinguishing media

Suitable extinguishing

media

Use any media suitable for the surrounding fires.

Unusual fire and explosion

hazard

The product is not flammable.

Protection of firefighters

Protective equipment and precautions for firefighters Wear suitable protective equipment.

6. Accidental Release Measures

Avoid contact with skin. Do not touch or walk through spilled material. Personal precautions

Use personal protective equipment to minimize exposure to skin and eye.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste Methods for cleaning up

container. Clean up in accordance with all applicable regulations.

Clean-up methods - small spillage; Flush area with flooding quantities of water.

7. Handling and Storage

Handling Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product.

Use personal protective equipment as required. Use only with adequate ventilation. When

using, do not eat, drink or smoke.

Storage Keep out of the reach of children. Keep tightly closed in a dry, cool and well-ventilated place.

Store at room temperature. Do not handle or store near an open flame, heat or other sources

of ignition.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH

Components	Туре	Value	Form
Diethanolamine (111-42-2)	TWA	2 mg/m3	
Glycerol (56-81-5)	TWA	10 mg/m3	Mist.
Isopropanol (67-63-0)	STEL	400 ppm	
,	TWA	200 ppm	

U.S. - OSHA

Components	Туре	Value	Form
Diethanolamine (111-42-2)	TWA	3 ppm 15 mg/m3	
Glycerol (56-81-5)	PEL	15 mg/m3 5 mg/m3	Total dust. Respirable fraction.

Material name CH158A MSDS US Creation date Nov 13, 2008 Version number 2 2/6



Components	Туре	Value	Form
	TWA	10 mg/m3	Total dust.
		5 mg/m3	Respirable fraction.
Isopropanol (67-63-0)	PEL	980 mg/m3	
		400 ppm	
	STEL	500 ppm	
		1225 mg/m3	
	TWA	400 ppm	
		980 mg/m3	

Personal protective equipment

Eye / face protection Wear safety glasses; chemical goggles (if splashing is possible). Eye wash fountain and

emergency showers are recommended.

Skin protection Wear appropriate chemical resistant clothing.

Wear appropriate chemical resistant gloves.

Respiratory protection Under normal conditions, respirator is not normally required.

Provide adequate ventilation.

General hygeine Handle in accordance with good industrial hygiene and safety practice. Avoid contact with considerations

skin, eyes and clothing.

When using, do not eat, drink or smoke. Wash hands before breaks and immediately after

handling the product.

Launder contaminated clothing before reuse.

9. Physical & Chemical Properties

Color Magenta Odor slight solvent **Odor threshold** Not available. **Physical state** Liquid.

Form Aqueous solution.

7 - 9 Hq

< 32 °F (< 0 °C) **Melting point** Freezing point Not available. 212 °F (100 °C) **Boiling point** Flash point Not flammable Not available. **Evaporation rate** Not available. **Flammability** Not available. Flammability limits in air, upper, % by volume

Flammability limits in air,

Not available.

lower, % by volume

Not available. Vapor pressure Not available. Vapor density

Not available. Specific gravity 1.04 g/cm³ Relative density Soluble Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature**

VOC 172.6 g/L



10. Chemical Stability & Reactivity Information

Chemical stability Stable under normal storage conditions.

Conditions to avoid Avoid high temperatures. Incompatible materials Strong oxidizing agents.

Possibility of hazardous

reactions

None known.

11. Toxicological Information

Sensitization

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (111-42-2) Can be absorbed through the skin.

Carcinogenicity

IARC Monographs on Occupational Exposures to Chemical Agents: Evidence of carcinogenicity in humans

Diethanolamine (111-42-2) Inadequate data. Isopropanol (67-63-0) Inadequate data.

US ACGIH Threshold Limit Values: A4 carcinogen

Isopropanol (67-63-0) Group A4 Not classifiable as a human carcinogen.

Symptoms and target organs

Target Organs (NIOSH)

Diethanolamine (111-42-2) Eyes

Diethanolamine (111-42-2) Respiratory system

Diethanolamine (111-42-2) Skin Glycerol (56-81-5) Eyes Glycerol (56-81-5) Kidneys

Glycerol (56-81-5) Respiratory system

Glycerol (56-81-5) Skin Isopropanol (67-63-0) Eves

Isopropanol (67-63-0) Respiratory system

Isopropanol (67-63-0) Skin

12. Ecological Information

Contains no substances known to be hazardous to the environment or not degradable in **Ecotoxicity**

waste water treatment plants.

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructions Dispose of in compliance with federal, state, and local regulations. Do not allow this material

to drain into sewers/water supplies.

14. Transport Information

IATA

Not regulated as dangerous goods.

General Not a regulated article under United States DOT, IATA, ADR, IMDG, or RID.

15. Regulatory Information

US federal regulations US EPA TSCA Inventory: All chemical substances in this product comply with all rules or

orders under TSCA.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Diethanolamine (111-42-2) 1.0 % Isopropanol (67-63-0) 1.0 %

CERCLA (Superfund) reportable quantity

None

Material name CH158A MSDS US Version number 2 Creation date Nov 13, 2008 4/6



Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

No

chemical

State regulations

US - New Jersey Community RTK (EHS Survey): Listed substance

Diethanolamine (111-42-2)

Isopropanol (67-63-0)

Substance no. 0686

Substance no. 1076

US - New Jersey Community RTK (EHS Survey): Reportable threshold

Diethanolamine (111-42-2) 500 LBS Isopropanol (67-63-0) 500 LBS US - Pennsylvania RTK - Hazardous Substances: Listed substance

 2-Pyrrolidone (616-45-5)
 Listed.

 Diethanolamine (111-42-2)
 Listed.

 Glycerol (56-81-5)
 Listed.

 Isopropanol (67-63-0)
 Listed.

16. Other Information

HMIS® ratings Health: 1

Flammability: 0 Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 0 Instability: 0

Issue date Mar 14 2009 1:10AM

Revision 2

Replaces sheet dated Feb 6 2009 5:47PM

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in

Section 1 above and may not meet regulatory requirements in other countries.

MSDS sections updated Hazards Identification: Eye contact

Hazards Identification: Skin contact

Accidental Release Measures: Personal precautions
 Regulatory Information: US federal regulations

Material name CH158A MSDS US

Creation date Nov 13, 2008 Version number 2 5 / 6



Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Manufacturer information Hewlett-Packard

11311 K-Tel Drive

Minnetonka, MN 55343 US

Product Information 1-800-925-0563

Material name CH158A MSDS US

Creation date Nov 13, 2008 Version number 2 6 / 6